

The technology parameter of [P10 Green color outdoor led module](#)

Best Quality Green color P10 led module

Specificaiton

Item	P10
Pixel pitch	10mm
Size of modual	160mm X 320 mm
Resolution of modual	16 X 32
Density of pixel	10000dots/m2
Pixel configuration	Green
Best viewing distance	10-120m
Horizontal viewing angle	110°
power consumption	420w/m2
Brightness	≥3000cd /m2
Control method	Asynchronization
Driving method	1/4scanning
Frame frequency	60Hz
Refresh frequency	≥300Hz
Working voltage	AC220V/110V±10%
IP grade	IP65(front)
Working temperature	-20°C~80°C
MTBF	>10000 hours
Life span	>100,000 hours
Defects rate.	≤0.00001(Led display line standard<0.0001)
What's app: 0086 18998946779 Skype:championled	

Usage:

The most popular for shops, companies.

Use for message borad, bar screen, LED banner sign.

Advantages:

1. Price Competitive,because we are large quantity make, daily output 20,000PCS
2. Time Advantages:always have stock
3. Quality Advantages: higher brightness, longer life

Delivery Time and packing:

1. Delivery time: Accomplish manufacturing within 3-7days after receiving the deposit.
- 2.Before delivery, we will test the display, and keep it light up for 24 hours, and check
- 3.Package:(1)Standard export carton (2) anti-shaking wooden case (3) flight case

Documents and Certification

1. We provide the software, packing list, Invoice and all docucments customer require
2. We can also provide all kinds of certification such as CE, ROHS, CCC and so on.

Guarantee

- (1) We guarantee all our displays, modules, parts for one year. During this time, we
- (2) We will provide maintenance for a lifetime and charge for the raw materials only.

Technology Training

- (1) We provide the technology training for free, which contains the operation training
- (2) We will send our engineers to your country by negotiation.

Certification:

CE

ROSH

CCC